

- Bacteriostatic
- Class A Fire Rating
- Easily Maintained
- Formable

- Non Porous (Mold Free)
- Durable
- Homogenous
- Repairable



Renewable

Reusable

Mineral Derivative

Weather & UV resistant

AVONITE™ is a solid surface material composed of 63% alumina trihydrate, 35% acrylic and 2% pigments and binders. It is produced at the Trinseo plant, in Florence (KY), USA, one of the most flexible and scalable production lines in the world. Trinseo relies on its experience and expertise to supply a reliable Solid Surface material.



RIGHT SIZE Program

Our Commitment to Ecology

Optimal Yield Sheet Sizes

Trinseo's RIGHT SIZE program for AVONITE™ Solid Surface provides the ultimate in flexibility, saving time and labor costs.

More details page 12

We see sustainability as more than just offering products with recycled content and regulatory compliance. It means having a responsibility to touch and improve lives by making a positive impact on others, now and for the future.

More details page 14

One of the Most Advanced **Production Technologies**

The ability of our continuous cast production lines to create a multi-stage system, incorporating controlled heating, cooling and tempering - all within one press enables the development of flexible and efficient solutions.



Our office in Florence, Kentucky was built in 1998. We used AVONITETM for the façade of our new building. Covered almost entirely in 0.25 in./6 mm thick AVONITETM Acrylic Solid Surface, the building remains a testament to the beauty and durability of our product.

Façade

The RIGHT SIZE program offers a competitive product portfolio that is perfectly suited to the creation of exterior façades.

For outdoor use, we recommend several colors of AVONITE™ Solid Surface that are UV and weather resistant.

CASA-VOYAGEURS TRAIN STATION, Casablanca, Morocco, 2019

Architecture: Yassir Khalil Studio

Fabrication: Aeria 2 Photo: alessiomei.com

AVONITE™ Snowfall 8090, 9 mm custom size sheet With over 25 000 sq. metres of Solid Surface, the new Casablanca train station is currently one of the industry's biggest construction sites in the world. Fully entrusted to AVONITE™, this project involves cladding the building's entire roof, façade and ceiling.







Architectural

AVONITE™ IS ABSOLUTELY VERSATILE.

It can be found on both the countertops and walls of ultra-clean labs and the overworked reception desks at hotels.

THAT'S NOT ALL.

AVONITETM is also used to produce flawless furniture for shops and museums.



Hygienic

The material's non-porous properties and the seamless assembly of furniture made of AVONITE™ makes it extremely easy to clean. Its thermoforming capacity also allows for the creation of rounded backsplashes on lab benches, kitchen counters and restaurant furniture, which eliminates those hard to reach places.

Durable

AVONITE™ is resistant to common household products and is easy to repair, thanks to the after sale servicing by one of our local partners. With its 15-year warranty on 12, 9 and 6 mm thicknesses and 10 year warranty on the 3 mm thickness, AVONITE™ will not fail you after your project is complete.



A Wide Range of Applications

TELUS SKY, Calgary, Canada

Photographer: Ema Peter Photography Fabricator: Heavy Industries, Walsh Plastics Architect: Bjarke Ingels Group & Dialog Developer: Westbank Developments AVONITE™ - 9 mm and 12 mm, Polaris 8256

en.wikipedia.org/wiki/Telus_Sky telussky.com

- Counters and backsplash
- Vanity tops
- Shower walls and bases
- Furniture
- Interior cladding
- Façade




ADVANC3™

With its sheets just 3 mm thick, AVONITE™ ADVANC3™ offers the properties and aesthetics of solid surface at reduced prices. It is a renewable hygienic surface that is great for hospital applications, modern furnishings, retail displays, and as a perfect substitute for high-pressure laminate. ADVANC3™ can only be used on installations with no heat source or water in proximity. Width options include 48 in. (122 cm) and 60 in. (152 cm) wide in a 96 in. (244 cm) length.

MADE TO ORDER COLORS:

- SUPER WHITE 8025
- **WHITE 8017**
- FOAM 8020
- SNOWFALL 8091

An excellent alternative to High Pressure Laminate, with all the benefits of solid surface. ADVANC3™ 3 mm is available in additional colors and custom sizes with minimum order quantities. Contact your representative for details.



AVONITE[™] **RIGHT SIZE** Program

Ultimate Flexibility

From the simplest format to the most unusual designs, AVONITE™ Solid Surface offers you an infinitely wide array of options to meet your project needs.

Personalized Sizing

With the RIGHT SIZE program, the choice is yours. We manufacture AVONITE™ directly to whatever width, length, thickness and color you choose.

- WIDTHS from 27 in. (685 mm) up to 60 in. (1524 mm)
- LENGTHS from 84 in. (2133 mm) up to 204 in. (5182 mm)
- CALIPER THICKNESS from 3 mm up to 19 mm
- Color and aesthetic, we'll work directly with your designer to bring their vision to life.

Saves Time

The use of large sheets reduces the number of seams required. Fewer seams mean less adhesive, less fabrication and simply put, less cost.


Sustainable Choice

The choice of an optimal format reduces scrap. Less scrap means less landfill, taking a step to help the environment.


Reach out to your Regional Manager today, to discuss Minimum Order Quantities based on your project needs.

LENGTH, WIDTH, THICKNESS, COLOR... You decide. The ultimate in flexibility for our customers.

Traditional Sheet Size



AVONITE™ RIGHT SIZE Sheet





2 134 x 686 mm

84 x 27 in. minimum dimensions

Thickness

3 mm / 0,12 in 6 mm / 0,24 in

9 mm / 0,35 in


12 mm / 0,47 in

19 mm / 0,75 in

5 182 x 1524 mm

204 x 60 in.

Sheets' maximum dimensions



Commitment to Ecology

We see sustainability as more than just offering products with recycled content and regulatory compliance – it means having a responsibility to touch and improve lives by making a positive impact on others, now and for the future.

Reuse and Recycle

At Trinseo, we continually strive to improve our energy and water efficiency, landfill diversion, and air quality, using performance metrics we measure and report. Recent and ongoing environmental initiatives, proactive recycling of office and industrial materials, high-efficiency motor upgrades to machine drives, industrial water filtration and recycling systems and thermal oxidizing units with heat recovery to reduce VOC emissions. Finally, Trinseo transport partner for Europe guarantees recycling of waste water, uses solar energy in the warehouse and trucks that run on gas.

Indoor Environmental Quality

AVONITE™ has been awarded Indoor Advantage Gold by SCS Global Services and earned a score of A+ for the material's adherence to French regulations governing the emission of volatile organic compounds.

Reducing Waste

The RIGHT SIZE program is another key component of our approach to sustainable design. Choosing the optimal sheet size format for your project reduces material square footage and also reduces or eliminates landfill.

Energy Conservation

Historically, it's not a coincidence if we chose to work with a double-belt continuous cast technology. Equipped with a symmetric heating and cooling system, solvent free and allowing to reduce the waste to the lowest level, this manufacturing technique is one of the eco-friendliest. Our Florence, Kentucky site was re-lamped with LED technology, significantly reducing electrical consumption.

Transparency and Disclosure

Expectations of transparency about the environmental and health impacts of building products are high in the green building market. Designers, specifiers and building owners want to know exactly what they are utilizing, encouraging the specification of products with documented declaration of contents and impacts. Trinseo provides transparency documentation through EPDs, HPDs, and one Declare Labels.

Health & Safety

AVONITE™ Solid Surface is Living Building Challenge Red List Free, containing none of the 800+ hazardous chemicals found in some building products. Using our silica-free solid surface material, means no risk of silica exposure during fabrication or installation.

Highlight





Honey Crunch 4330

Coastline 4310



Certifications:









Our Color Selection

From the simple elegance of Kokoura to the purity of Snowfall or the vitality of Oxbow, AVONITE™ offers a color range balanced between trends and timeless classics.


12 mm Solid Surface



Legend

The tones shown on this page may differ slightly from the actual colors. To be safe, make your choice based on samples.

- Minimum order quantities will apply to these Made to Order (MTO) colors.
- These colors are heavily pigmented and prone to show scratches, haziness and ordinary wear and tear compared to lighter colors. These colors are not recommended for use in heavy traffic or heavy use applications and will not be covered under the AVONITE™ warranty for ordinary wear and tear.
- Contains Recycled Content. Colors marked with this acronym include recycled material and may therefore qualify for additional credits as part of the building's LEED accreditation.
- Riverine is an expansive, free-flowing marble pattern that varies from sheet to sheet. Each sheet is unique.





Enriched Color Technology

Our AVONITE™ Enriched Color Technology delivers a more intense color and its mechanical properties improve scratch resistance. Available in Eclipse 8240.

Private residence, Belgium, 2020 Design and fabrication: Denis Margot AVONITE™ Eclipse 8240

Our Color Selection (cont'd)

3 mm Solid Surface - ADVANC3™

Super White 8025 White 8017 Snowfall 8091 Foam 8020

9 mm Solid Surface



6 mm Solid Surface - Wet Wall



Additional Legacy Colors

These made to order legacy colors are available in minimum order quantities. Contact your representative for details.



Technical Information

Made in the USA

AVONITE™ Solid Surface, manufactured in Florence, Kentucky, is in full compliance with the Build America, Buy America Act (BABAA) requirements.

Capacity

AVONITE™ has been a pioneer in the surface industry for over 50 years. Trinseo has the largest continuous cast manufacturing facility in the world, with 4 lines that are 9 ft. (2.75 m) wide and 300 ft. (91 m) long.



Chemical Datasheet

To determine stain and chemical resistance, chemical reagents are placed on the surface for 16 hours*. After the 16 hours period, reagents are removed using the cleaning methods described in the Technical Bulletin 201 (ISFA 2-01 and ANSI/ICPA SS-1 standards).

Stain Resistance

Stain resistance looks at the effect below the surface. The following reagents show no lasting effects on the surface of AVONITETM sheets when tested to the ISFA 2-01 cleanability/stain resistance standard:

Acetic Acid (10%)	Dishwasher Detergent	3%	Naphtha	Tomato Juice
Acetone	(Cascade)	Instant Coff	Olive Oil	Trisodium Phosphate (5%)
B-4 Body Conditioner	Dishwashing Liquid	Isopropyl Alcohol (90%)	Pencil Lead	Urea (6 %)
Ball Point Ink Pen	Distilled Water	Lemon Juice	Permanent Marker	Vegetable Oil
Black Paste Shoe Polish	Ethanol	Lye Solution (1-2%)	Pig Blood	Vinegar
Bleach (Household Type)	Ethyl Alcohol (90%)	Mercurochrome (2%)	Pine Oil	Wax Crayon
Butyl Acetate	Finger Nail Polish Remover	Methanol	Povidone Iodine (10 %)	Wet Pekoe Tea Bag
Butyl Alcohol	Gasoline	Methyl Acetate	Yellow Mustard	Wine
Butyl Ether	Household bleach	Methyl Ethyl Ketone	Sodium Sulfate (10%)	Xylene
Catsup	Household Ammonia	Methyl Orange (1%)	Soy Sauce	Zinc Chloride (10%)
Citric Acid (10%)	Hydrogen Peroxide	Methyl Red (1%)	Sugar (sucrose)	
Cupra Ammonia	Hydrogen Peroxide Solution,	Mineral Oil	Toluene	

Chemical Resistance

Chemical resistance is a measure of visible surface changes. The following reagents show no lasting effects on the surface of AVONITE™ Acrylic Solid Surface sheets when tested to the ANSI/ICPA SS-1 standard:

Acetic Acid (10%)	(Household Type)	Hexane	Olive Oil	Sugar (Sucrose)
Acetone	Blood	Household Soaps	Pencil Lead	Tea
Acridine Orange	Butyl Acetate	Hydrogen Peroxide	Perchloric Acid	Toluene
AG Eosin Blue (5%)	Butyl Alcohol	Hydrogen Peroxide Solution	Permanent Marker Ink	Tomato Juice
AG Gentian Violet	Butyl Ether	(3%)	Picric Acid	Trisodium Phosphate (5%)
Ammonia (10 %)	Catsup	Instant Coffee	Pig Blood	Urea (6 %)
Ammonium Hydroxide	Citric Acid (10%)	Isopropyl Alcohol (90%)	Pine Oil	Uric Acid
(28%)	Coffee	Lemon Juice	Povidone Iodine (10%)	Urine
Amyl Acetate	Cupra Ammonia	Lye Solution (1-2%)	Yellow Mustard	Vegetable Oil
Amyl Alcohol	Dishwashing Liquid	Mercurochrome (2%)	Salt (Sodium Chloride)	Vinegar
Aromatic Ammonia	(Cascade)	Methanol	Silica Dental Cement (liquid)	Wax Crayon
B-4 Body Conditioner	Dishwashing Liquid (Dawn)	Methyl Acetate	Silver Nitrate (10%)	Wet Pekoe Tea Bag
Ball Point Pen	Distilled Water	Methyl Ethyl Ketone	Soapless Detergents	Wine
Betadine Solution	Equalizing Accelerator	Methyl Orange (1%)	Sodium Bisulfate	Xylene
Bite Registration Accelorator	Ethanol	Methyl Red (1%)	Sodium Hydroxide Solution	Zinc Chloride (10%)
(2% Eugenol)	Ethyl Acetate	Mineral Oil	(<10 %)	
Bite Registration Base	Ethyl Alcohol (90%)	Naphtha	Sodium Hypochlorite (5%)	
Black Paste Shoe Polish	Nail Polish Remover	Napthalene (Naptha)	Sodium Sulfate (10 %)	
Bleach	Gasoline	Nitric Acid (6%)	Soy Sauce	

The following reagents should not come into contact with AVONITE™ sheets for long periods of time. These reagents may cause surface changes on the sheets that are more difficult to remove:

· Bite Registration Mix	· Dry-Bond Dental Adhesive	· Eosine Methylene Blue	· Nitric Acid (>25 %)	Sulfuric Acid (>25%)
(50/50)		 Hydrochloric Acid (>20 %) 	· Sodium Hydroxide Solution	
		· Nail Polish	(>25%)	

^{*}Although the 16 hours period is standard test procedure, it is recommended to remove chemicals as soon as possible, to prevent damage to the surface.

Physical Properties

AVONITE™ Acrylic Solid Surface Sheets

Trinseo AVONITE™ Acrylic Solid Surface sheet products provide exceptionally weatherable, strong, non-porous, scratch and stain resistant material for architectural designs and utilitarian surfaces.

eneral ensity ASTM D 792 g/cm³ 1.73 0.04 0.04 0.04 0.04 0.04 0.04 0.04 0.04 0.05 1.05				3 mm	6 mm	9 mm
ASTM D 792 g/cm³ 1.73 1.73 1.73 1.73 1.73 1.73 Aster Absorption ASTM D 570 % 0.13 0.04 0.04 Aster Absorption ASTM D 638 MPa 3.3.4 31.1 31.1 Aster Absorption ASTM D 638 MPa 3.3.4 31.1 31.1 Aster Absorption ASTM D 638 MPa 7010 10.514 10.514 Bensile endudus ASTM D 638 MPa 7010 10.514 10.514 Bensile elongation ASTM D 638 MPa 7010 10.514 10.514 Beautral strength ASTM D 790 MPa 71.0 64.1 64.1 Beautral modulus ASTM D 790 MPa 71.0 64.1 64.1 Beautral modulus ASTM D 790 MPa 71.0 64.1 64.1 Beautral modulus ASTM D 790 MPa 71.0 64.1 64.1 Beautral modulus ASTM D 790 MPa 6070 8687 8687 Beat all impact (227g ball, no failure) ASTM D 785 — 86 94 94 Beat all impact (227g ball, no failure) NEMA LD3-3.8 cm 3-80 380 3-80 Beat all impact (227g ball, no failure) Unsupported NEMA LD3-3.8 cm 3-380 3-380 Beat all impact (227g ball, no failure) Unsupported NEMA LD3-3.8 cm 3-380 3-380 Beat all impact (227g ball, no failure) Unsupported NEMA LD3-3.8 cm 3-380 3-380 Beat all impact (227g ball, no failure) Unsupported NEMA LD3-3.8 cm 3-380 3-380 Beat all impact (227g ball, no failure) Unsupported NEMA LD3-3.8 cm 3-380 3-380 Beat all impact (227g ball, no failure) Unsupported NEMA LD3-3.8 cm 3-380 3-380 Beat all impact (227g ball, no failure) Unsupported NEMA LD3-3.8 cm 3-380 3-380 Beat all impact (227g ball, no failure) Unsupported NEMA LD3-3.8 cm 3-380 3-380 Beat all impact (237g ball, no failure) Unsupported NEMA LD3-3.8 cm 3-380 3-380 Beat all impact (237g ball, no failure) Unsupported NEMA LD3-3.8 cm 3-380 3-380 Beat ASTM D 648	Property	Test Method	Units	Solids	Solids	Solids
ASTM D 570	General		·	·	·	
Rechanical ASTM D 638 MPa 33.4 31.1 31.1 ensile strength ASTM D 638 MPa 7010 10514 10514 ensile elongation ASTM D 638 MPa 7010 0.40 0.40 exerral modulus strength ASTM D 790 MPa 71.0 64.1 64.1 exerral modulus ASTM D 790 MPa 6070 8687 8687 arcol hardness ASTM D 2583 - 59 63 63 ockwell hardness (m scale) ASTM D 785 - 86 94 94 harry pimpact ASTM D 6110 J/m 104.0 58.7 58.7 all impact (227g ball, no failure) NEMA LD3-3.8 cm - - - 305 all Impact (227g ball, no failure) Unsupported NEMA LD3-3.8 cm 213 215 - bermal tul @ 1.82 Mpa ASTM D 648 °C 88 102 102 cefficient of thermal expansion ISFA 2-01 - No Effect </td <td>Density</td> <td>ASTM D 792</td> <td>g/cm³</td> <td>1.73</td> <td>1.73</td> <td>1.73</td>	Density	ASTM D 792	g/cm³	1.73	1.73	1.73
ASTM D 638 MPa 33.4 31.1 31.1 ansile modulus ASTM D 638 MPa 7010 10.514 10.514 ansile modulus ASTM D 638 MPa 7010 10.514 10.514 ansile modulus ASTM D 638 MPa 7010 10.514 10.514 ansile elongation ASTM D 638 MPa 7010 10.514 10.514 ansile elongation ASTM D 638 MPa 7010 64.1 64.1 ansile elongation ASTM D 790 MPa 7010 64.1 64.1 ansile elongation ASTM D 790 MPa 6070 8.687 8.687 arcol hardness ASTM D 790 MPa 6070 8.687 8.687 arcol hardness MSTM D 780 MPa 6070 8.687 8.687 arcol hardness (m.scale) ASTM D 785 — 86 94 94 94 94 94 ASTM D 785 — 86 94 94 94 94 ASTM D 785 — 86 94 94 94 94 94 94 94 94 94 94 94 94 94	Water Absorption	ASTM D 570	%	0.13	0.04	0.04
ASTM D 638 MPa 7010 10514 10514 2051	Mechanical					
ensile elongation	Tensile strength	ASTM D 638	MPa	33.4	31.1	31.1
dexural strength ASTM D 790 MPa of 71.0 64.1 64.1 of 4.1 dexural modulus ASTM D 790 MPa of 6070 8687 8687 arcol hardness ASTM D 2583 — 59 63 63 ockwell hardness (m scale) ASTM D 6110 J/m 104.0 58.7 58.7 all impact (227g ball, no failure) NEMA LD3-3.8 cm — 380 — 380 — 380 all Impact (227g ball, no failure) Supported NEMA LD3-3.8 cm — 380 — 380 — 380 all Impact (227g ball, no failure) Unsupported NEMA LD3-3.8 cm — 380 — 380 — 305 all Impact (227g ball, no failure) Unsupported NEMA LD3-3.8 cm — 380 — 380 — 380 — 380 — 6 — 6 — 6 — 6 — 6 — 6 — 7	Tensile modulus	ASTM D 638	MPa	7010	10514	10514
dexural modulus ASTM D 790 MPa 6070 8687 8687 arcol hardness ASTM D 2583 - 59 63 63 ockwell hardness (m scale) ASTM D 785 - 86 94 94 harpy impact ASTM D 6110 J/m 104.0 58.7 58.7 all impact (227g ball, no failure) NEMA LD3-3.8 cm - - 305 all Impact (227g ball, no failure) Unsupported NEMA LD3-3.8 cm - - 305 all Impact (227g ball, no failure) Unsupported NEMA LD3-3.8 cm - - - 305 all Impact (227g ball, no failure) Unsupported NEMA LD3-3.8 cm - - - 305 all Impact (227g ball, no failure) Unsupported NEMA LD3-3.8 cm - - - 305 - all Impact (227g ball, no failure) Unsupported NEMA LD3-3.8 cm - - - - - - - - - - - -	Tensile elongation	ASTM D 638	%	1.40	0.40	0.40
ASTM D 2583 - 59 63 63 63 63 64 64 64 64 64 64 64 64 64 64 64 64 64	Flexural strength	ASTM D 790	MPa	71.0	64.1	64.1
ASTM D 785 - 86 94 94 harpy impact ASTM D 6110 J/m 104.0 58.7 58.7 all impact (227g ball, no failure) NEMA LD3-3.8 cm 305 all Impact (227g ball, no failure) Supported NEMA LD3-3.8 cm - 380 380 all Impact (227g ball, no failure) Supported NEMA LD3-3.8 cm 213 215 hermal Iul @ 1.82 Mpa ASTM D 648 °C 88 102 102 oefficient of thermal expansion ASTM D 696 cm/cm/°C - 3.76×10-5 3.76×10-5 oiling water resistance ISFA 2-01 - No Effect No Effect No Effect igh temperature resistance ISFA 2-01 - No Effect No Effect No Effect of the ormal	Flexural modulus	ASTM D 790	MPa	6070	8 687	8 6 8 7
harpy impact ASTM D 6110 J/m 104.0 58.7 58.7 all impact (227g ball, no failure) NEMA LD3-3.8 cm 305 all Impact (227g ball, no failure) Supported NEMA LD3-3.8 cm - 310 all Impact (227g ball, no failure) Unsupported NEMA LD3-3.8 cm - 213 all Impact (227g ball, no failure) Unsupported NEMA LD3-3.8 cm - 213 all Impact (227g ball, no failure) Unsupported NEMA LD3-3.8 cm - 213 all Impact (227g ball, no failure) Unsupported NEMA LD3-3.8 cm - 213 all Impact (227g ball, no failure) Unsupported NEMA LD3-3.8 cm - 213 all Impact (227g ball, no failure) Unsupported NEMA LD3-3.8 cm - 213 all Impact (227g ball, no failure) Unsupported NEMA LD3-3.8 cm - 213 all Impact (227g ball, no failure) Unsupported NEMA LD3-3.8 cm - 213 all Impact (227g ball, no failure) Supported NEMA LD3-3.4 cm - 213 all Impact (227g ball, no failure) Supported NEMA LD3-3.4 cm - 213 all Impact (227g ball, no failure) Supported NEMA LD3-3.4 cm - 213 all Impact (227g ball, no failure) Supported No growth No growth No growth undirect Supported Nema LD3-3.4 cm - 245 all Impact (227g ball, no failure) Supported NEMA LD3-3.4 cm - 245 all Impact (227g ball, no failure) Supported NEMA LD3-3.4 cm - 245 all Impact (227g ball, no failure) Supported NEMA LD3-3.4 cm - 245 all Impact (227g ball, no failure) Supported Nema LD3-3.4 cm - 245 all Impact (227g ball, no failure) Supported No growth No growth undirect Supported Nema LD3-3.4 cm - 245 all Impact (227g ball, no failure) Supported Nema LD3-3.4 cm - 245 all Impact (227g ball, no failure) Supported Nema LD3-3.4 cm - 245 all Impact (227g ball, no failure) Supported No growth No growth undirect Supported Nema LD3-3.4 cm - 245 all Impact (227g ball, no failure) Supported Nema LD3-3.4 cm - 245 all Impact (227g ball, no failure) Supported Nema LD3-3.4 cm - 245 all Impact (227g ball, no failure) Supported No failure)	Barcol hardness	ASTM D 2583	-	59	63	63
all impact (227g ball, no failure) NEMA LD3-3.8 cm 305 all Impact (227g ball, no failure) Supported NEMA LD3-3.8 cm >380 >380 380 380	Rockwell hardness (m scale)	ASTM D 785	_	86	94	94
ASTM D 6116 Organic Compounds ASTM D 5116 Pittsburgh Protocol Pitt	Charpy impact	ASTM D 6110	J/m	104.0	58.7	58.7
ASTM D 648 °C 88 102 102 oefficient of thermal expansion ASTM D 648 °C NO Effect NO Effect Igh temperature resistance ISFA 2-01 - No Effect NO Ef	Ball impact (227g ball, no failure)	NEMA LD3-3.8	cm	-	-	305
hermal tul @ 1.82 Mpa	Ball Impact (227g ball, no failure) Supported	NEMA LD3-3.8	cm	>380	>380	-
ASTM D 648 °C 88 102 102 oefficient of thermal expansion ASTM D 696 cm/cm/°C - 3.76x10-5 3.76x10-5 oiling water resistance ISFA 2-01 - No Effect No Effect No Effect igh temperature resistance ISFA 2-01 - No Effect No Effect No Effect eaction to fire ASTM E 84 - Class B Class A Class A ombustion toxicity Pittsburgh Protocol - 98 98 98 otal Volatile Organic Compounds ASTM D 5116 µg/m²/hr 69.1 69.1 69.1 onsistency of color (same sheet) ISFA 2-01 - No Effect No Effect leanability/Stain resistance ISFA 2-01 - No Effect No Effect No Effect leanability/Stain resistance ANZI/ICPA SS-1 - Passes Passes Passes acterial resistance ASTM G 22 - No growth No growth No growth lungi resistance ASTM G 21 - No growth No growth No growth	Ball Impact (227g ball, no failure) Unsupported	NEMA LD3-3.8	cm	213	215	-
oefficient of thermal expansion ASTM D 696 cm/cm/°C - 3.76x10-5 3.76x10-5 oiling water resistance ISFA 2-01 - No Effect N	Thermal					
oiling water resistance ISFA 2-01 - No Effect No Effec	Dtul @ 1.82 Mpa	ASTM D 648	°C	88	102	102
igh temperature resistance eaction to fire ASTM E 84 - Class B Class A Class A combustion toxicity Pittsburgh Protocol - 98 98 98 98 otal Volatile Organic Compounds ASTM D 5116 pg/m²/hr 69.1 69.1 69.1 purface ISFA 2-01 - Passes Passes Passes Passes ight resistance ISFA 2-01 - No Effect No Effect No Effect No Effect leanability/Stain resistance NEMA LD3-3.4 - Passes Passes Passes Passes acterial resistance ANZI/ICPA SS-1 - No growth No growth No growth ungi resistance ASTM G 22 - No growth No	Coefficient of thermal expansion	ASTM D 696	cm/cm/°C	-	3.76x10 ⁻⁵	3.76x10 ⁻⁵
eaction to fire ASTM E 84 — Class B Class A Class A Class A ombustion toxicity Pittsburgh Protocol — 98 98 98 ptal Volatile Organic Compounds ASTM D 5116 µg/m²/hr 69.1 69.1 69.1 purface ISFA 2-01 — Passes	Boiling water resistance	ISFA 2-01	_	No Effect	No Effect	No Effect
Pittsburgh Protocol – 98 98 98 98 ptal Volatile Organic Compounds ASTM D 5116 μg/m²/hr 69.1 69.1 69.1 69.1 purface ISFA 2-01 – Passes Passes Passes ight resistance ISFA 2-01 – No Effect No Effect leanability/Stain resistance NEMA LD3-3.4 – Passes Passes Passes tain resistance ANZI/ICPA SS-1 – Passes Passes Passes acterial resistance ASTM G 22 – No growth No growth No growth ungi resistance ASTM G 21 – No growth No growth No growth	High temperature resistance	ISFA 2-01	_	No Effect	No Effect	No Effect
onsistency of color (same sheet) ISFA 2-01 Isf	Reaction to fire	ASTM E 84	_	Class B	Class A	Class A
urface ISFA 2-01 - Passes Passes Passes ight resistance ISFA 2-01 - No Effect No Effect No Effect leanability/Stain resistance ISFA 2-01 - No Effect No Effect No Effect leanability/Stain resistance ISFA 2-01 - Passes Passes Passes Passes ANZI/ICPA SS-1 - Passes Passes Passes acterial resistance ISFA 2-01 - No growth No growth No growth Indignate Indigna	Combustion toxicity	Pittsburgh Protocol	_	98	98	98
onsistency of color (same sheet) ISFA 2-01 - Passes Passes Ight resistance ISFA 2-01 - No Effect No Eff	Total Volatile Organic Compounds	ASTM D 5116	μg/m²/hr	69.1	69.1	69.1
ight resistance ISFA 2-01 - No Effect No Effect No Effect leanability/Stain resistance NEMA LD3-3.4 - Passes Passes Passes tain resistance ANZI/ICPA SS-1 - Passes Passes Passes acterial resistance ASTM G 22 - No growth No growth No growth ungi resistance ASTM G 21 - No growth No growth No growth	Surface					
leanability/Stain resistance NEMA LD3-3.4 - Passes Passes Passes Passes tain resistance ANZI/ICPA SS-1 - Passes Passes Passes Passes P	Consistency of color (same sheet)	ISFA 2-01	-	Passes	Passes	Passes
tain resistance ANZI/ICPA SS-1 - Passes Passes Passes acterial resistance ASTM G 22 - No growth No growth ungi resistance ASTM G 21 - No growth No growth No growth	Light resistance	ISFA 2-01	-	No Effect	No Effect	No Effect
ASTM G 22 - No growth No growth ungi resistance ASTM G 21 - No growth No growth No growth No growth	Cleanability/Stain resistance	NEMA LD3-3.4	-	Passes	Passes	Passes
ungi resistance ASTM G 21 – No growth No growth No growth	Stain resistance	ANZI/ICPA SS-1	-	Passes	Passes	Passes
	Bacterial resistance	ASTM G 22	-	No growth	No growth	No growth
ood zone use	Fungi resistance	ASTM G 21	-	No growth	No growth	No growth
	Food zone use	NSF 51	-	Approved	Approved	Approved

	12 mm								
	Solids	Small Particulate	Medium Particulate	Large Particulate	AVONITE™ 8064 IceWhite 8298 Ice Blue				
	1.73	1.60	1.62	1.63	1.60				
	0.04	0.05	0.05	0.05	0.05				
	31.1	31.1	28.3	25.2	30.7				
	10514	7142	8 4 1 1	8204	8650				
	0.40	1.00	0.55	0.45	2.20				
	64.1	55.2	49.3	47.2	58.3				
	8 6 8 7	7329	7240	8067	7010				
	63	58	59	60	55				
	94	94	93	93	92				
	58.7	58.7	45.3	42.7	59.8				
	>380	305	290	215	>380				
	-	-	-	-	-				
	-	-	-	-	-				
	102	93	93	92	100				
	3.76x10 ⁻⁵	4.43x10 ⁻⁵	4.43x10 ⁻⁵	4.43x10 ⁻⁵	-				
	No effect								
	No effect								
	Class A	Class A	Class A	Class A	Class B				
	98	67	67	67	98				
	69.1	69.1	69.1	69.1	69.1				
	Passes	Passes	Passes	Passes	Passes				
	No effect								
	Passes	Passes	Passes	Passes	Passes				
	Passes	Passes	Passes	Passes	Passes				
1	No growth								
1	No growth								
	Approved	Approved	Approved	Approved	Approved				



trinseo.com

The principles of Responsible Care® and sustainability influence the production of printed literature for Trinseo PLC and its affiliated companies. As a contribution toward the protection of our environment, Trinseo's printed literature is produced in small quantities and on paper containing recovered/post-consumer fiber and using 100 percent soy-based ink whenever possible.

Product Stewardship

Trinseo and its affiliated companies have a fundamental concern for all who make, distribute, and use their products and for the environment in which we live. This concern is the basis for our Product Stewardship philosophy by which we assess the safety, health, and environmental information on our products so that appropriate steps may be taken to protect employee and public health and our environment. The success of our product stewardship program rests with each and every individual involved with Trinseo products - from the initial concept and research, to manufacture, use, sale, disposal, and recycle of each product.

Customer Notice

Customers are responsible for reviewing their manufacturing processes and their applications of Trinseo products from the standpoint of human health and environmental quality to ensure that Trinseo products are not used in ways for which they are not suitable. Trinseo personnel are available to answer questions and to provide reasonable technical support. Trinseo product literature, including safety data sheets, should be consulted prior to the use of Trinseo products. Current safety data sheets are available from

No freedom from infringement of any patent owned by Trinseo or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, the customer is responsible for determining whether products and the information in this document are appropriate for the customer's use and for ensuring that the customer's workplace and disposal practices are in compliance with applicable legal requirements. Although the information herein is provided in good faith and was believed to be accurate when prepared, Trinseo assumes no obligation or liability for the information in this document.

NOTICE REGARDING MEDICAL APPLICATION RESTRICTIONS

TRINSEO REQUESTS THAT CUSTOMERS REFER TO TRINSEO'S MEDICAL APPLICATION POLICY HTTP://WWW.TRINSEO.COM/MEDICAL.HTM BEFORE CONSIDERING THE USE OF TRINSEO PRODUCTS IN MEDICAL APPLICATIONS. THE RESTRICTIONS AND DISCLAIMERS SET FORTH IN THAT POLICY ARE INCORPORATED BY REFERENCE.

For more information on products, innovations, expertise, and other services available from Trinseo, visit www.trinseo.com, or in the U.S. contact us at +1-855-TRINSEO (+1-855-874-6736).

DISCLAIMER

TRINSEO MAKES NO WARRANTIES, EITHER EXPRESS OR IMPLIED, IN THIS DOCUMENT; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE (INCLUDING MEDICAL APPLICATIONS) ARE EXPRESSLY EXCLUDED. SINCE THE CONDITIONS AND METHODS OF USE OF THE INFORMATION AND PRODUCTS REFERRED TO ARE BEYOND TRINSEO'S KNOWLEDGE AND CONTROL, TRINSEO DISCLAIMS ANY AND ALL LIABILITY FOR LOSSES OR DAMAGES THAT MAY RESULT FROM RELIANCE ON THE INFORMATION OR USE OF THE PRODUCTS DESCRIBED HEREIN. TRINSEO MAKES NO WARRANTIES, EXPRESS OR IMPLIED, THAT THE USE OF ANY TRINSEO PRODUCT WILL BE FREE FROM ANY INFRINGEMENT CLAIMS.

GENERAL NOTICE

Any photographs of end-use applications in this document represent potential end-use applications but do not necessarily represent current commercial applications, nor do they represent an endorsement by Trinseo of the actual products. Further, these photographs are for illustration purposes only and do not reflect either an endorsement or sponsorship of any other manufacturer for a specific potential end-use product or application, or for Trinseo, or for specific products manufactured by Trinseo.If products are described as "experimental" or "developmental": (1) product specifications may not be fully determined; (2) analysis of hazards and caution in handling and use are required; (3) there is greater potential for Trinseo to change specifications and/or discontinue production, and (4) although Trinseo may from time to time provide samples of such products, Trinseo is not obligated to supply or otherwise commercialize such products for any use or application whatsoever.

For additional information not covered by the content of this document or to ensure you have the latest version of this document available, please refer to our website at www.trinseo.com/Contact-Us.

Follow us at:













Copyright© Trinseo (2024) All rights reserved. ™Trademark of Trinseo PLC or its affiliates ®Responsible Care is a service mark of the American Chemistry Council.

